

DESCRIPTION

WONDER-HIDE™ Interior Latex Paint is a quick-drying, economical paint that can be tinted to many colors, making it ideal for new or existing property maintenance and commercial applications. Designed for use on interior walls, ceilings and trim surfaces, Wonder-Hide paint delivers high production with good dry hide. This quality interior paint's ease of application improves project efficiency.

FEATURES/BENEFITS

Features	Benefits
Easy application	Saves time on the project
Fast drying	Can be topcoated as soon as four hours
Durable finish	Easy maintenance of painted surface

SPECIFICATION DATA*

*Specification data calculated on DR53325

Bases & Colors:

DR53325 – High Hiding White

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

Finish:

Flat

Clean-up Solvent:

Soap & water

Resin:

Vinyl Acrylic Resin

Density:*

10.62 lbs/gal (1.27 kg/L)

VOC:

<50 g/L (0.42 lbs/gal)

Solids:*

Volume - 22% +/- 1%

Weight - 39% +/- 1%

Practical Coverage:

Apply at 300-400 sq ft/gal.

(28 - 37 sq. meters) per U.S. gallon.

Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:

4.0 - 5.3 mils wet

0.9 - 1.2 mils dry

Flame Spread Rating:

Class A (0-25) over non-combustible surfaces

Flash Point:

None

Dry Time 77°F (25°C) & 50% RH:

To touch – 1 hour

To recoat - 4 hours

Shelf Life:

1 year minimum - unopened

SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES: Drywall - Prime with latex wall primer DR50801. Product may be used self-priming, used as a primer under itself. Concrete, Masonry and Plaster - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Must be internally dry. Remove loose aggregate. Prime concrete with all-purpose primer DRP51801. Product may also be used self-priming on concrete, used as a primer under itself. Fill concrete block with a latex block filler. Prime plaster with all-purpose primer DRP51801. Wood - Set nails, fill with latex spackle. Sand smooth. Dust clean. Prime with the appropriate latex or alkyd wood primer. Steel - Prime with the appropriate waterborne or solventborne metal primer. Galvanized Metal and Aluminum - Prime with the appropriate waterborne or solventborne metal primer.

PREVIOUSLY PAINTED SURFACES: Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Remove loose paint. Prime bare areas with primer specified under NEW SURFACES.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

TINTING: Tint the appropriate base with universal colorants.

SPREADING RATE: Apply at approximately 300-400 sq. ft. (28 - 37 sq. meters) per U.S. gallon (3.78 L) on primed, smooth, nonporous surfaces. Coverage figures do not include material loss due to application. For best hiding, tint primers toward finish coat color. Some colors, drastic color changes, or porous surfaces may require additional coats to achieve a uniform finish.

APPLICATION: Mix thoroughly before use. May be applied by brush (synthetic), roller (3/8" to 1/2" nap) or spray. No thinning required. For airless spray application, use tip size .015" - .021" and pressure range of 1500 – 2000 psi. Adjust pressure as needed. When using more than one container of the same color, intermix to ensure color uniformity. Do not thin. Apply when air, product, and

surface temperatures are 50°F (10°C) or above. Provide good ventilation and warmth for normal drying.

DRYING TIME: Normally dries to touch in one hour at 77°F (25°C) and 50% relative humidity. Allow 4 hours before recoating. Drying times listed may vary depending on temperature, humidity, color, film build and air movement.

CLEAN-UP: Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

DISPOSAL: **Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.**

PRECAUTIONS

WARNING! HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF INHALED. Sanding and grinding dusts may be harmful if inhaled. Contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Contains material that may cause target organ damage, based on animal data. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling. Keep container tightly closed and sealed until ready for use. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

SHIPPING

FREIGHT CLASSIFICATION:
DO NOT FREEZE

PACKAGING:
1 gallon (3.785)
5 gallons (18.925 L)

FLASH POINT:
None



PPG Pittsburgh Paints and The Drippy P Design are registered trademarks of PPG Architectural Finishes, Inc. The PPG Logo is a trademark of PPG Industries Ohio, Inc. Wonder-Hide is a trademark of AkzoNobel.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our website or call 1-800-441-9695.