

DESCRIPTION

PVA Interior Latex Primer is a fine-quality interior PVA latex primer/sealer for use on interior drywall, acoustic ceiling tiles and popcorn ceilings. It may also be used on concrete and masonry walls. It is high-hiding and sandable.

SPECIFICATION DATA\*

Bases:

DRN53360 – White (tintable up to 2 oz.)

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

Finish:

Flat, 2.5 – 6.5 units @ 85°

Clean-up Solvent:

Soap & water

Resin:

Vinyl-Acrylic Resin

Density:

10.91 lbs/gal (1.30 kg/L)

VOC:

<50 g/L (0.42 lbs/gal)

Solids:

Volume - 24% +/- 1%

Weight - 42% +/- 1%

Practical Coverage:

Apply at 250-300 sq ft/gal.

(23 - 28 sq. meters) per U.S. gallon.

Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:

5.3 - 6.4 mils wet

1.3 - 1.5 mils dry

Flame Spread Rating:

Class A (0-25) over non-combustible surfaces

Flash Point:

None

Dry Time 77°F (25°C) & 50% RH

To touch – 30 minutes

To recoat – 1 hour

Shelf Life:

1 year minimum - unopened

FEATURES/BENIFITS

Features	Benefits
Easy application	Saves time on the project
Fast drying	Can be topcoated as soon as two hours

## SURFACE PREPARATION

**GENERAL SURFACE PREPARATION:** All surfaces must be sound, dry, clean and free of oil, grease, dirt, rust, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

**NEW SURFACES:** Drywall - Joint compound must dry for two days before priming. Remove sanding dust. Prime with this product. Concrete, Masonry and Plaster - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Remove loose aggregate. Prime with this product or a masonry bonding primer. Fill block with a latex block filler. Prime plaster with a masonry bonding primer. **Not recommended for use on Wood, Steel, Galvanized Metal and Aluminum surfaces.** Wood - Sand smooth and dust clean. Prime with an interior latex wood primer. Steel - Prime with a metal primer. Galvanized Metal and Aluminum - Prime with a galvanized metal primer.

**PREVIOUSLY PAINTED SURFACES:** Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under **NEW SURFACES**. Porous flat finishes must be sealed with this product.

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

## DIRECTIONS FOR USE

**TINTING:** White may be tinted with up to two oz./gal. of universal colorants.

**SPREADING RATE:** Apply at approximately 300-400 sq. ft. (28 - 37 sq. meters) per U.S. gallon (3.78 L) on primed, smooth, nonporous surfaces. Coverage figures do not include material loss due to application. For best hiding, tint primers toward finish coat color. Some colors, drastic color changes, or porous surfaces may require additional coats to achieve a uniform finish.

**APPLICATION:** Mix thoroughly before use. May be applied by brush (synthetic), roller (3/8" to 1/2" nap) or spray. No thinning required. For airless spray application, use tip size .015" - .021" and pressure range of 1500 - 2000 psi. Adjust pressure as needed. When using more than one container of the same color, intermix to ensure color uniformity. Do not thin. Apply when air,

product, and surface temperatures are 50°F (10°C) or above. Provide good ventilation and warmth for normal drying.

**DRYING TIME:** Normally dries to touch in 30 minutes at 77°F (25°C) and 50% relative humidity. Allow one hour before recoating. Drying times listed may vary depending on temperature, humidity, color, film build and air movement.

**CLEAN-UP:** Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

**DISPOSAL:** **Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.**

## PRECAUTIONS

**WARNING! HARMFUL IF SWALLOWED. CAUSES RESPIRATORY TRACT AND EYE IRRITATION. MAY BE HARMFUL IF INHALED.**

Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Contains material that may cause target organ damage, based on animal data. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling. Keep container tightly closed and sealed until ready for use. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

## SHIPPING

**FREIGHT CLASSIFICATION:**  
DO NOT FREEZE

**PACKAGING:**  
4 quart (0.9168 L)  
1 gallon (3.785)  
5 gallons (18.925 L)  
Not all products are available in all sizes

**FLASH POINT:**  
None



PPG Pittsburgh Paints and The Drippy P Design are registered trademarks of PPG Architectural Finishes, Inc.. The PPG Logo is a trademark of PPG Industries Ohio, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our website or call 1-800-441-9695.